



MODEL	Years	Air Spring	Kit Part #	SINGLE AIR	DUAL AIR
CHEVROLET/GMC					
C & R 10, 20 1500 (4X2 ONLY)	73-87	6781	2071*	2097	2219
C & K 1500 SILVERADO/SIERRA (4X2, 4X4)	99-06	9000	2320++	2158	2178
C&K 2500HD,3500 Silverado/Sierra (4X2, 4X4)	11-15	6401	2528	2097	2219
C&K 2500HD,3500 Silverado/Sierra (2WD,4WD)	01-10	6781	2250	2097	2219
C & K 2500HD, 3500 (4X2, 4X4) Cab&Chassis	01-10	6781	2249	2097	2219
VAN & CLASS C MOTORHOME					
G30,3500 FRONT	70-95	6000	4100		
CLASS A MOTORHOME					
GP-30 HD (CUTAWAY) 10,500 TO 12,300, 14,500 FRONT	93-96	6000	4100		
DODGE					
RAM 1500 MEGA CAB (4X2,4X4)	06-08	6401	2299	2097	2219
RAM 2500(2WD, 4WD) w/ Contact Overloads	94-98	6781	2220	2158	2178
RAM 2500,3500 (4X2,4X4)	94-02	6781	2071*	2158	2178
RAM 2500,3500 (4X2,4X4)	03-12	6401	2299	2097	2219
RAM 2500 (4X2,4X4)	2013	6401	2299	2097	2219
RAM 3500 (4X2,4X4)	2013	6401	2560	2097	2219
RAM D3500, W3500 Cab & Chassis (2 & 4 WD)	94-02	6781	2220	2158	2178
FORD					
F150 (4X2,4X4)	68-96	6781	2071*	2158	2178
F150, 250 UNDER 8500 SUPERCREW (04 Heritage)	97-03	9000	2320++	2158	2178
F150 (4x2,4x4) not Raptor or FX2	09-14	6781	2525	2097	2219
F250, F350 (2 WD, 4 WD), Diesel	11-14	6401	2535	2097	2219
F250, F350 (2 WD, 4 WD), Gasoline	11-14	6401	2550	2097	2219
F250, F350 (2 WD, 4 WD), Gasoline w/ In Bed Hitch	11-14	6401	2520	2097	2219
F250, F350 (2 WD, 4 WD)	08-10	6401	2550	2097	2219
F250, F350 Over 8500 GVW (2 WD, 4 WD) w/o HITCH	05-07	6401	2452	2097	2219
F250, F350 Over 8500 GVW (2 WD, 4 WD)	99-04	6401	2550	2097	2219
F350 (2 WD) Gasoline (Not V10 w/Ext Cab & 8' Bed	11-14	6401	2550	2097	2219
F350 (2 WD) Not V10 w/Ext Cab & 8' Bed	99-04	6401	2550	2097	2219
F250 OVER 8500 GVWR, F350 (2WD,4WD)	69-10	6781	2071*	2097	2219
F250 OVER 8500 GVWR (2WD,4WD), F350 (2WD) w/ In Bed Hitch	05-07	6401	2398	2097	2219
F350 (4X4) w/in bed hitch	05-07	6401	2400	2097	2219
E250	92-10	9002	2165	2158	2178
E450 requires 2" clearance above frame	96-09	6781	2153+	2097	2168
NISSAN					
TITAN (4x2,4x4)	04-09	6781	2355	2158	2178
TOYOTA					
TACOMA (4X2)	05-10	6762	2410	2158	2178

Notice: Firestone has made every attempt to assure that the ride-rite kits listed will properly fit. Chassis modifications made by others that effect suspension dimensions may not provide conditions for proper fit. Due to new model introductions and manufacturer changes, Firestone reserves the right to make changes to this list with out notice.

SEE PAGE 109 FOR OPTIONAL AIR CONVENIENCE SYSTEMS & PAGE 108 FOR REPLACEMENT SPRINGS

Do NOT exceed the vehicles Recommended Gross Vehicle Weight Rating (GVWR)

REQUIREMENTS

- * REQUIRES 7.50" OF CLEARANCE BETWEEN THE FRAME AND TIRE BOTH SINGLE AND DUAL REAR WHEELS
- ** REQUIRES 3.00" OF CLEARANCE BETWEEN THE FRAME AND TIRE
- *** REQUIRES 9.50" OF CLEARANCE BETWEEN THE FRAME AND TIRE
- + REQUIRES 8.00" OF CLEARANCE BETWEEN THE FRAME AND TIRE
- ++ IF VEHICLE HAS LESS THAN 7.50" OF CLEARANCE BETWEEN FRAME AND TIRE SEE KIT 2099
- +++ REQUIRES 6.25" OF CLEARANCE BETWEEN THE FRAME AND TIRE
- ++++ REQUIRES 6.50" OF CLEARANCE BETWEEN THE FRAME AND TIRE