



# AXLE MEASUREMENT CHARTS

USE AS A GUIDE WHEN ORDERING AXLES — (ALL MEASUREMENTS IN INCHES)



**ALKO T-20 2000 lb. AXLE**

Track	Hub Face	1-3/4" Straight Axle		2-3/8" Straight Axle		Overall Length	Outside Flanges
48	49	33.75	to 39.00	29	to 37.25	54"	41.75"
50	51	35.75	to 41.00	31	to 39.25	56"	43.75"
52	53	37.75	to 43.00	33	to 41.25	58"	45.75"
54	55	39.75	to 45.00	35	to 43.25	60"	47.75"
56	57	41.75	to 47.00	37	to 45.25	62"	49.75"
58	59	43.75	to 49.00	39	to 47.25	64"	51.75"
60	61	45.75	to 51.00	41	to 49.25	66"	53.75"
62	63	47.75	to 53.00	43	to 51.25	68"	55.75"
64	65	49.75	to 55.00	45	to 53.25	70"	57.75"
66	67	51.75	to 57.00	47	to 55.25	72"	59.75"
68	69	53.75	to 59.00	49	to 57.25	74"	61.75"
70	71	55.75	to 61.00	51	to 59.25	76"	63.75"
72	73	57.75	to 63.00	53	to 61.25	78"	65.75"
74	75	59.75	to 65.00	55	to 63.25	80"	67.75"
76	77	61.75	to 67.00	57	to 65.25	82"	69.75"
78	79	63.75	to 69.00	59	to 67.25	84"	71.75"
80	81	65.75	to 71.00	61	to 69.25	86"	73.75"
82	83	67.75	to 73.00	63	to 71.25	88"	75.75"
84	85	69.75	to 75.00	65	to 73.25	90"	77.75"
86	87	71.75	to 77.00	67	to 75.25	92"	79.75"
88	89	73.75	to 79.00	69	to 77.25	94"	81.75"
90	91	75.75	to 81.00	71	to 79.25	96"	83.75"
92	93	77.75	to 83.00	73	to 81.25	98"	85.75"

**ALKO T-35,D-35 3500 lb. AXLE**

Track	Hub Face	Spring Center Straight Axle		Spring Center Drop Axle		Overall Length	Outside Flanges
58	59	42	to 47.75	40	to 44.12	63.75	52.88
60	61	44	to 49.75	42	to 46.12	65.75	54.88
62	63	46	to 51.75	44	to 48.12	67.75	56.88
64	65	48	to 53.75	46	to 50.12	69.75	58.88
66	67	50	to 55.75	48	to 52.12	71.75	60.88
68	69	52	to 57.75	50	to 54.12	73.75	62.88
70	71	54	to 59.75	52	to 56.12	75.75	64.88
72	73	56	to 61.75	54	to 58.12	77.75	66.88
74	75	58	to 63.75	56	to 60.12	79.75	68.88
76	77	60	to 65.75	58	to 62.12	81.75	70.88
78	79	62	to 67.75	60	to 64.12	83.75	72.88
80	81	64	to 69.75	62	to 66.12	85.75	74.88
82	83	66	to 71.75	64	to 68.12	87.75	76.88
84	85	68	to 73.75	66	to 70.12	89.75	78.88
86	87	70	to 75.75	68	to 72.12	91.75	80.88
88	89	72	to 77.75	70	to 74.12	93.75	82.88
90	91	74	to 79.75	72	to 76.12	95.75	84.88
92	93	76	to 81.75	74	to 78.12	97.75	86.88
94	95	78	to 83.75	76	to 80.12	99.75	88.88