




<i>Part Number</i>	<i>Style</i>	<i>Height</i>	<i>Tire Size</i>	<i>Capacity (lbs.)</i>	<i>Load Range</i>
<b>4 on 4 Bolt Circle</b>					
DC844W/T	White Disc	16"	480×8	590	B
21-1220W/T	White Spoke	20.5"	480×12	780	B
91-1220W/530C	White Mod.	20.5"	530×12	1045	C
<b>5 on 4.5 Bolt Circle</b>					
DC8545W/T	White Disc	16"	480×8	590	B
DC8545W/570T	White Disc	18"	570×8	715	B
62004C-W/T	White Disc	18.5"	18.5×8.5×8	940	C
62005C-W/T	White Disc	20.5"	20.5×8×10	1105	C
62005E-W/T	White Disc	20.5"	20.5×8×10	1535	E
91-12545W/T	White Mod.	20.5"	480×12	780	B
91-12545-530C	White Mod.	22"	530×12	1045	C
28-3412W/T	Galv. Spoke	23"	ST175/80D13	1065	B
91-3412W/T	White Mod.	23"	ST175/80D13	1065	B
MT1314K55C	Chrome Spoke	23"	ST175/80D13		C
91-4612W/T	White Mod.	25"	ST205/75D14	1710	C
MTT14205C-W1460G	Galv. Spoke	25"	ST205/75R14	1710	C
21-5612W/T	White Spoke	27"	ST205/75D15C	1820	C
91-5612W/205R	White Mod.	27"	ST205/75R15	1820	C
91-5612W/205R	White Mod.w/Radial	27"	ST205/75R15	1820	C
MTSS15205C-W1550G	Galv. Spoke	27"	ST205/75R15	1820	C
<b>5 on 5.0 Bolt Circle</b>					
91-5050W/T	White Mod	27"	ST205/75D15C	1820	C
<b>6 on 5.5 Bolt Circle</b>					
91-5660W/205R	White Mod.w/Radial	27"	ST205/75R15	1820	C
91-5660W/225R	White Mod.w/Radial	27.5"	ST225/75R15	2540	D
MTSS15225D-W1560G	Galv. Spoke	27.5"	ST225/75R15	2540	D
96-5660W/T	Chrome Mod.	27.5"	ST225/75D15	2540	D
91-6550W/T	White Mod.	30.8"	ST235/75R16	3500	E
<b>8 on 6.5 Bolt Circle</b>					
91-7680W/T	White Mod.	30.8"	ST235/80R16	3500	E
1667G	White Mod.	31.7"	LT235/85R16	3760	G

**5-LUG BOLT CIRCLES**


Measure from center of wheel or hub to center of one bolt hole or stud. N double that number for true bolt circle

