



<i>Part Number</i>	<i>Capacity per pair (lbs.)</i>	<i>Number of Leafs</i>	<i>Stack Height (in.)</i>	<i>Width (in.)</i>	<i>Eye to Eye (A) Length (in.)</i>
AS2	900	2	.50	1 <sup>3</sup> / <sub>4</sub>	26
AS3	1350	3	.81	1 <sup>3</sup> / <sub>4</sub>	26
AS4	1800	4	1.00	1 <sup>3</sup> / <sub>4</sub>	26
AWS2 (09318204)	1500	2	.75	1 <sup>3</sup> / <sub>4</sub>	26
AWS3 (8144)	3000	3	1.25	1 <sup>3</sup> / <sub>4</sub>	26
AWS4 (093153)	4000	4	1.64	1 <sup>3</sup> / <sub>4</sub>	26
SW4B (8103)	3500	4	1.13	1 <sup>3</sup> / <sub>4</sub>	25 <sup>1</sup> / <sub>4</sub>
AWS5 (093155)	5000	5	2.00	1 <sup>3</sup> / <sub>4</sub>	26
AWS6 (09315450)	6000	6	2.19	1 <sup>3</sup> / <sub>4</sub>	26
AWS7 (093154)	7000	7	2.50	1 <sup>3</sup> / <sub>4</sub>	26
AWS8	7100	8	2.88	1 <sup>3</sup> / <sub>4</sub>	26
ML4/MR4 (8106)	6000	4	1.63	1 <sup>3</sup> / <sub>4</sub>	25.125"
SW6	7000	6	2.00	1 <sup>3</sup> / <sub>4</sub>	25 <sup>1</sup> / <sub>4</sub>

***Dexter/AL-KO***

72-6	2500	3	.94	1 <sup>3</sup> / <sub>4</sub>	23 <sup>1</sup> / <sub>4</sub>
72-9 (8116)	3500	3	1.08	1 <sup>3</sup> / <sub>4</sub>	23.125"
72-13 (093178)	2800	4	1.10	1 <sup>3</sup> / <sub>4</sub>	20 <sup>1</sup> / <sub>4</sub>
72-16	1400	3	.67	1 <sup>3</sup> / <sub>4</sub>	20 <sup>1</sup> / <sub>4</sub>
72-17 (8117)	2000	3	.79	1 <sup>3</sup> / <sub>4</sub>	20 <sup>1</sup> / <sub>4</sub>
72-20 (093183)	5000	4	1.44	1 <sup>3</sup> / <sub>4</sub>	23 <sup>1</sup> / <sub>4</sub>
72-22 (8122)	2500	3	.94	1 <sup>3</sup> / <sub>4</sub>	25 <sup>1</sup> / <sub>4</sub>
72-23 (8102)	3000	3	1.04	1 <sup>3</sup> / <sub>4</sub>	25 <sup>1</sup> / <sub>4</sub>
72-24 (8121)	4000	3	1.16	1 <sup>3</sup> / <sub>4</sub>	25 <sup>1</sup> / <sub>4</sub>
72-25 (8105)	5000	4	1.50	1 <sup>3</sup> / <sub>4</sub>	25 <sup>1</sup> / <sub>4</sub>
72-26	6000	4	1.64	1 <sup>3</sup> / <sub>4</sub>	25 <sup>1</sup> / <sub>2</sub>
72-27 (8114)	7000	6	2.05	1 <sup>3</sup> / <sub>4</sub>	24.875"
8108	6000	5	2.01	1 <sup>3</sup> / <sub>4</sub>	25 <sup>1</sup> / <sub>4</sub>

***Slipper Springs***

					<i>Slipper (B) Length (in.)</i>
BT25-9 (8142)	1900	3	.78	1 <sup>3</sup> / <sub>4</sub>	25
72-30 (8112)	4000	4	1.33	2	26
72-31 <small>(1003T3)</small>	5000	4	1.44	2	26 <sup>1</sup> / <sub>8</sub>
72-32 <small>(1203T3)</small> (8109)	7000	5	1.80	2	26 <sup>1</sup> / <sub>8</sub>
72-43-1 (8131)	10000	5	1.90	3	30
72-44-1 (8132)	12000	6	2.10	3	30
8139 <small>(1403T3)</small>	8000	7	2.52	2	26 <sup>1</sup> / <sub>8</sub>